

Tonmind SIP Paging Adapter SIP-T20

1. Two-way intercom communication
2. Support 48K OPUS Audio Codec
3. SIP & Onvif protocol compatibility
4. Pre recorded message(WAV/MP3)
5. Alarm: GPIO, HTTP URL, and relay out
6. MIC, headset and speaker interface
7. Reset and volume control



Specification:

Audio

Codec OPUS 48 kHz, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz

Network

Security Password protection, IP address filtering, Digest authentication, User access log, firewall

Network Protocol SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP

Network Interface 10/100 Base-TX, RJ45

Support for SIP protocol for intergration with VoIP systems, intergrated with SIP/PBX.

VoIP 2 SIP Accounts, SIP Direct IP Call, RTP Multicast

Codec: OPUS, MP3, G.722, PCMU, PCMA

Amplifier

Amplifier description Built-in 15W Amplifier

General

Material Metal

Power Supply PoE or DC 12V/24V

Interface 1* MIC input, 1* Headset output, 1* Speaker output, 2* GPIO input, 1* Relay output, 1*GPIO output

Dimensions 112mm *105mm * 29mm

Weight 250g

Languages English

Warranty 2 years

Package includes SIP Paging Adapter
User Manual